


THROUGH CONNECTORS

for Copper conductors



L-M



Conductor Size sqmm		Type	Dimensions mm		Quantity Box/Bag	Mechanical Tools	Hydraulic Tools
Low Stranded	Flexible		Øi	L			
0,25÷1,5	0,25÷1,5	L03-M*	1,8	15	6.000/100	HN1 HN5 HN-A25 TN70SE TN120 SE* B15MDE HT45-E B450ND-BVE HT51 B550E RH450 B500E B500NDE HT81-U RHU81 HT120 and tools and heads with 130 kN crimping force ECW-H3D RHU520	
1,5÷2,5	1,5÷2,5	L06-M*	2,4	15	4.000/100		
4÷6	4÷6	L1-M*	3,6	22	2.000/100		
10	10	L2-M	4,6	25	1.000/100		
16	16	L3-M	5,8	27	1.000/100		
25	25	L5-M	7,0	29	500/100		
35	25÷35	L7-M	8,9	33	400/100		
50	35÷50	L10-M	10,0	37	200/50		
70	50÷70	L14-M	11,3	39	200/50		
95	70÷95	L19-M	13,5	43	100/25		
120	95÷120	L24-M	15,2	47	100/25		
150	120÷150	L30-M	16,7	58	50/25		
185	150÷185	L37-M	19,2	64	50/25		
240	185÷240	L48-M	21,1	75	30/15		
300	240÷300	L60-M	23,7	90	20/10		
400	300÷400	L80-M	27,0	94	15/5		
500	400÷500	L100-M	30,3	98	12/1		
630	500÷630	L120-M*	33,4	105	12/1		
800	600	L160-M*	38,0	112	9/1		
1000	800	L200-M*	44,0	120	6/1		

L-M range of connectors are designed for jointing low voltage conductors,

Made of electrolytic Copper tube having the same dimension as A-M series lugs: L-M connectors are annealed and electrolytically Tin plated. They feature an internal taper at both ends to ease the introduction of the conductor and a central stop to ensure correct positioning.

Details of the appropriate crimping tools and dies are shown on pages 206 to 207.