

**Raychem heat-shrinkable medium voltage terminations IXSU-F/OXSU-F for indoor and outdoor applications for polymeric cables up to 42 kV**

## 12 kV



**Termination for crimp lug  
Screened single core plastic and rubber cable**

Cross section [mm <sup>2</sup> ]	Kit number Indoor	Kit number Outdoor	Diameter over insulation HD 620 A2 [mm]
10 - 35	IXSU-F 3111	OXSU-F 3111	16.3
25 - 95	IXSU-F 3121	OXSU-F 3121	13.7 - 20.8
95 - 240	IXSU-F 3131	OXSU-F 3131	18.6 - 28.4
240 - 500	IXSU-F 3141	OXSU-F 3141	25.7 - 36.2
500 - 800	IXSU-F 3151	OXSU-F 3151	34.0 - 42.2
800 - 1200	IXSU-F 3161	OXSU-F 3161	39.5 - 50.0

**Termination with mechanical lug BLMT  
Screened single core plastic and rubber cable**

Cross section [mm <sup>2</sup> ]	Kit number Indoor	Kit number Outdoor	Diameter over insulation HD 620 A2 [mm]
25 - 35	IXSU-F3111-ML-1-13	OXSU-F3111-ML-1-13	13.7 - 16.3
	IXSU-F3111-ML-1-17	OXSU-F3111-ML-1-17	
25 - 95	IXSU-F3121-ML-1-13	OXSU-F3121-ML-1-13	13.7 - 20.8
	IXSU-F3121-ML-1-17	OXSU-F3121-ML-1-17	
95 - 240	IXSU-F3131-ML-4-13	OXSU-F3131-ML-4-13	18.6 - 28.4
	IXSU-F3131-ML-4-17	OXSU-F3131-ML-4-17	
120 - 300	IXSU-F3131-ML-5-13	OXSU-F3131-ML-5-13	20.1 - 30.4
	IXSU-F3131-ML-5-17	OXSU-F3131-ML-5-17	
185 - 400	IXSU-F3141-ML-6-13	OXSU-F3141-ML-6-13	23.2 - 33.6
	IXSU-F3141-ML-6-17	OXSU-F3141-ML-6-17	
500 - 630	IXSU-F3151-ML-7-17	OXSU-F3151-ML-7-17	34.4 - 40.0
	IXSU-F3151-ML-7-21	OXSU-F3151-ML-7-21	

## 12 kV


**Termination for crimp lug  
Screened 3-core plastic and rubber cable without armour**

Cross section [mm <sup>2</sup> ]	Tail Length [mm]	Kit number Indoor	Kit number Outdoor
10 - 16	450	IXSU-F 3301	OXSU-F 3301
	1200	IXSU-F 3304	OXSU-F 3304
16 - 35	450	IXSU-F 3311	OXSU-F 3311
	1200	IXSU-F 3314	OXSU-F 3314
25 - 70	450	IXSU-F 3321	OXSU-F 3321
	1200	IXSU-F 3324	OXSU-F 3324
95 - 240	450	IXSU-F 3331	OXSU-F 3331
	1200	IXSU-F 3334	OXSU-F 3334
240 - 500	450	IXSU-F 3341	OXSU-F 3341
	1200	IXSU-F 3344	OXSU-F 3344

**Termination with mechanical lug BLMT  
Screened 3-core plastic and rubber cable without armour**

Cross section [mm <sup>2</sup> ]	Tail Length [mm]	Kit number Indoor	Kit number Outdoor
25 - 35	450	IXSU-F3311-ML-1-13	OXSU-F3311-ML-1-13
		IXSU-F3311-ML-1-17	OXSU-F3311-ML-1-17
	1200	IXSU-F3314-ML-1-13	OXSU-F3314-ML-1-13
		IXSU-F3314-ML-1-17	OXSU-F3314-ML-1-17
25 - 70	450	IXSU-F3321-ML-1-13	OXSU-F3321-ML-1-13
		IXSU-F3321-ML-1-17	OXSU-F3321-ML-1-17
	1200	IXSU-F3324-ML-1-13	OXSU-F3324-ML-1-13
		IXSU-F3324-ML-1-17	OXSU-F3324-ML-1-17
95 - 240	450	IXSU-F3331-ML-4-13	OXSU-F3331-ML-4-13
		IXSU-F3331-ML-4-17	OXSU-F3331-ML-4-17
	1200	IXSU-F3334-ML-4-13	OXSU-F3334-ML-4-13
		IXSU-F3334-ML-4-17	OXSU-F3334-ML-4-17
300 - 400	450	IXSU-F3341-ML-6-13	OXSU-F3341-ML-6-13
		IXSU-F3341-ML-6-17	OXSU-F3341-ML-6-17
		IXSU-F3341-ML-6-21	OXSU-F3341-ML-6-21
	1200	IXSU-F3344-ML-6-13	OXSU-F3344-ML-6-13
		IXSU-F3344-ML-6-17	OXSU-F3344-ML-6-17
		IXSU-F3344-ML-6-21	OXSU-F3344-ML-6-21