

3M™ Scotchcast™ Resin

Resin Solutions for Low-Voltage Splicing, Insulating and Sealing.

We have your solution for everyday cable connection tasks.

We've made this proven solution from 3M cleaner and easier to use. 3M™ Scotchcast™ Polyurethane Resin 40 now comes with a one-part mould that allows for a cleaner and more reliable application. Our ready-to-mix package contains two ideal proportions of resin, ready to combine. Thanks to the integrated spout and nozzle, the mix can be applied practically mess-free.





3M[™] Scotchcast[™] Polyurethane Resin 40

3M™ Scotchcast™ Polyurethane Resin 40 is suitable for electrical insulation and protection against environmental influences for low-voltage electrical splice joints up to 0.6/1.0 (1.2) kV.

Discover the advantages of 3M™ Scotchcast™ Polyurethane Resin 40:

- The closed mix and pour system ensures minimal spillage, precise application and a reduced risk of contact with the resin
- One-piece mould for fast, reliable and mess-free installation
- Low exothermic heat formula that prevents the cables from being damaged
- Applicable with larger cross-section cables
- Provides strong mechanical protection
- Available in a wide variety of sizes and with different types of moulds for various applications

Application Range [mm²] for different kit sizes using either Resin 40

In-Line Splice

3M™ Scotchcast™ Polyurethane Resin 40	Cu			AI				Cu		⊗ mm		
Kit Reference	Application Range in mm ²		Application Range in mm ²				Application Range in mm ²		Application Range in O.D.			
92-NBA x series	4	×	5	×	4	×	5	×	4 × c	or 5 ×	m	m
92-NBA 0	1,5	4	1,5	2,5	-	_		_		_	4	16
92-NBA 1	1,5	10	1,5	6	-	-	-	_	-	_	10	22
92-NBA 2	6	16	2,5	10	-	-		-	-	-	12	25
92-NBA 3	16	25	6	16	-	_	-	_	-	_	13	32
92-NBA 4	25	50	16	35	16	35	16	25		-	18	36
92-NBA 5	50	95	25	50	35	70	25	50	-	-	19	45
92-NBA 6	70	120	50	95	70	120	50	95	-	-	27	54
92-NBA 7	120	240	95	150	95	240	95	150	-	-	29	64
92-NBA 1C (w/Conn)		_		_	-	_		_	1,5	6	10	22
92-NBA 3C (w/Conn)		-		-		-		-	1,5	16	10	32

T-Branch Splice

3M™ Scotchcast™ Polyurethane Resin 40	A									
Kit Reference	Application Range in mm ²		mm²	Application Range in mm ²				Application Range in O.D.		
92-NBC series	4 × Main Cable		4 × Branch Cable		5 × Main Cable		5 × Branch Cable		mm	
92-NBC 2	4	35	4	25	2,5	25	2,5	25	16	33
92-NBC 2C (w/Conn)	4	16	4	16	2,5	16	2,5	16	16	33

Application Range [mm²] for different kit sizes using either Resin 40

Y-Branch Splice

Kit Reference	Application Range in mm ²			Ар	plication	Application Range in O.D.				
92-NBB x series	4 × Main Cable		4 × Branch Cable		5 × Main Cable		5 × Branch Cable		mm	
92-NBB 0	1,5	4	1,5	4	-	-	-	-	9	18
92-NBB 1	2,5	16	2,5	16	1,5	10	1,5	10	11	23
92-NBB 2	4	35	4	35	2,5	25	2,5	25	16	33
92-NBB 1C (w//Conn)	25	16	2,5	25	1,5	10	1,5	10	11	23
92-NBB 2C (w/Conn)	4	10	4	10	2,5	16	2,5	16	16	33

3M™ Scotchcast™ Polyurethane Resin 40



Kit Reference	ml	Nozzle
RESIN 40 BAG SIZE A	90	Υ
RESIN 40 BAG SIZE B	200	Υ
RESIN 40 BAG SIZE C	370	Υ

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application.

As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. Warranty, Limited Remedy, and Disclaimer: A limitation of liability applies to the 3M product(s). For warranty statement and limitation of liability, refer to your supply agreement or the 3M terms & conditions of sale.

Not for consumer sale or use. For additional product information, visit 3M Global Gateway (3M.com).



3M United Kingdom PLC 3M Centre Cain Road, Bracknell Berkshire RG12 8HT www.3m.co.uk

3M Ireland Limited The Iveagh Building Carrickmines Park, Carrickmines, Dublin 18 www.3mireland.ie **3M a/s** Hannemanns Allé 53 DK-2300 København S Denmark www.3mdanmark.dk

Suomen 3M Oy Keilaniementie 1 02150 ESPOO PL 600, 02151 ESPOO puh. 09 525 21 Finland www.3msuomi.fi 3M Norge AS Tærudgata 16 2004 Lillestrøm Norway www.3mnorge.no

3M Svenska AB Herrjärvatorg 4 170 67 Solna Sweden www.3msverige.se